



# C19

## LOCKABLE OUTLET

### Technical Information



#### General Information

- Snap-in mounting from front
- Solder terminal or quick connect from single terminal
- Protection class 1
- Integral plug retention feature

#### Technical Data

**Rating:** 16A/250VAC

**Insulation Resistance:**  
10MΩ (500VDC, 1 Min.)

**Dielectric Strength:**  
2KV (50Hz 1 Min) to accessible surfaces

**Materials Socket:**  
Black Thermoplastic UL94V-0

#### Approvals

16 A/250VAC: ENEC 05, KEMA KEUR

20 A/250VAC: UL

#### Patent

**UK Number:** 2463468B

**EU Number:** EP2321879A

**HK Number:** HK1141901

**Chinese Patent Application No:**  
CN 102150330 A

Other worldwide patents pending

#### Product

- Black & White IEC320 Snap in 1mm or 1.5mm Panel Thickness
- Quick Connector/Solder 6.3 x 0.8mm

#### Standards

IEC/EN 60320-2-2/FUL498

CSA C22.2 No 182.3-M1987

**Scolmore**  
GROUP

visit: [www.ieclock.com](http://www.ieclock.com)

call: +44 (0)1827 63454

email: [oemsales@scolmore.com](mailto:oemsales@scolmore.com)

**ConMec**

Tlf; 21 08 80 00

[post@conmec.no](mailto:post@conmec.no)

[www.conmec.no](http://www.conmec.no)